



Typical Applications

- Kitchens
- Food Processing Areas
- Restaurants
- Public houses
- Hotels

Description

- Steel Body
- Duco black enamel paint finish inside and out
- Internal flow control
- BSP threaded inlet and outlet connections

Model	Flow Rate (Ltrs/Sec)	Grease Storage (Kg)	Meals (Per day)	L	W	H	Invert	In/Outlet (BSP)
GT 50	1.0	13.5	50	650	400	400	100	2"
GT 65	1.25	18.0	65	725	425	430	140	3"
GT 90	1.50	22.0	90	750	450	500	150	3"
GT 120	2.25	32.0	120	825	500	550	175	3"
GT 150	3.25	42.0	150	900	550	600	200	3"

Note 1

These units are designed to be free standing or cast into kitchen floors, NOT suitable for external underground installation



Croom, Enmore Road, Enmore, Bridgwater, Somerset. TA5 2AN
 Tel: 01278 671927 Fax: 01278 671963 E-mail: info@synergy-wtp.co.uk
 Web: www.synergy-wtp.co.uk

Drawing Title:

Grease Trap
 (Free standing under sink unit
 see note1)

Revision Details:

Drawing No.

SD0922

Date:

October 2009

All dimensions are in mm

Scale: NTS

Drawn by: